



Radial Leaded PTC Resettable Fuse : FRVL Series

1. Summary

- (a) RoHS Compliant (Lead Free) product
- (b) Applications : Wide variety of electronic equipment
- (c) Product Features : Solid state, Radial leaded product ideal for up to 135V_{AC/DC}
- (d) Operation Current : 100mA~3.75A
- (e) Maximum Operating Voltage : 120V_{AC/DC}
- (f) Maximum Interrupt Voltage : 135V_{AC/DC}
- (g) Temperature Range : -40°C to 85°C

2. Agency Recognition

UL、C-UL: File No. E211981

FRVL010-120F、FRVL075-120F、FRVL135-120F、FRVL160-120F、FRVL185-120F and
FRVL200-120F

Other Model: Pending

3. Electrical Characteristics (23°C)

Part Number	Hold Current I _H , A	Trip Current I _T , A	Max.Time to Trip at 5X I _H , Sec	Maximum Current I _{max} , A	Rated Voltage V _{max} , V	Typical Power Pd, W	Resistance Tolerance	
							Rmin ohms	R1max. ohms
FRVL010-120F	0.10	0.20	10.0	2.0	120	0.84	3.00	7.50
FRVL017-120F	0.17	0.34	10.0	2.0	120	0.84	2.00	7.00
FRVL020-120F	0.20	0.40	9.0	2.0	120	1.08	1.83	4.40
FRVL025-120F	0.25	0.50	7.5	3.0	120	1.08	1.25	3.00
FRVL030-120F	0.30	0.60	8.5	3.0	120	1.44	0.88	2.10
FRVL040-120F	0.40	0.80	6.5	3.0	120	1.44	0.55	1.29
FRVL050-120F	0.50	1.00	6.0	3.0	120	1.56	0.50	1.17
FRVL065-120F	0.65	1.30	5.7	5.0	120	1.68	0.31	0.72
FRVL070-120F	0.75	1.50	6.3	5.0	120	1.80	0.25	0.60
FRVL075-120F	0.75	1.50	15.0	7.5	120	2.64	0.25	0.69
FRVL090-120F	0.90	1.80	7.2	5.0	120	1.80	0.20	0.47
FRVL100-120F	1.00	2.00	15.0	10.0	120	2.64	0.18	0.47
FRVL110-120F	1.10	2.20	8.2	8.0	120	2.28	0.15	0.38
FRVL125-120F	1.25	2.50	20.0	12.5	120	2.88	0.11	0.33
FRVL130-120F	1.35	2.70	9.6	10.0	120	2.64	0.12	0.30
FRVL135-120F	1.35	2.70	20.0	13.5	120	3.12	0.11	0.30
FRVL160-120F	1.60	3.20	11.4	12.0	120	3.12	0.09	0.22
FRVL185-120F	1.85	3.70	12.6	12.0	120	3.36	0.08	0.19
FRVL200-120F	2.00	4.20	36.0	20.0	120	4.32	0.08	0.21
FRVL250-120F	2.50	5.00	15.6	15.0	120	4.44	0.05	0.13
FRVL300-120F	3.00	6.00	19.8	17.0	120	4.56	0.04	0.10
FRVL375-120F	3.75	7.50	24.0	20.0	120	4.80	0.03	0.08

I_H=Hold current-maximum current at which the device will not trip at 23°C still air.

I_T=Trip current-minimum current at which the device will always trip at 23°C still air.

V_{MAX}=Maximum voltage device can withstand without damage at its rated current.

I_{MAX}= Maximum fault current device can withstand without damage at rated voltage (V_{MAX}).

NOTE : Specification subject to change without notice.



Pd=Typical power dissipated from device when in tripped state in 23°C still air environment.

R_{MIN}=Minimum device resistance at 23°C.

R_{1MAX}=Maximum device resistance at 23°C, 1 hour after tripping .

Physical specifications:

Lead material: Tin plated copper,24AWG、22AWG、20AWG

Soldering characteristics:MIL-STD-202, Method 208E.

Insulating coating:Flame retardant epoxy, meets UL-94V-0 requirement.









4. Production Dimensions (millimeter)

Fig 1.

Fig 2.

Fig 3.

Fig 4.



FRVL010-120F~FRVL017-120F
Lead S ize :24AWG
Φ 0.51 mm Diameter

FRVL020-120F~FRVL090-120F
Lead Size :22AWG
Φ 0.65 mm Diameter

FRVL110-120F~FRVL375-120F
Lead Size :20AWG
Φ 0.81 mm Diameter


FRVL075-120F ~FRVL200-120F
Lead Size : 20AWG
Φ 0.81 mm Diameter

Part Number	Figure	A	B	C	D	E	F
		Maximum	Maximum	Typical	Minimum	Maximum	Typical
FRVL010-120F	1	7.9	13.0	5.1	7.6	3.8	2.2
FRVL017-120F	1	7.9	13.0	5.1	7.6	3.8	2.2
FRVL020-120F	2	7.9	13.0	5.1	7.6	3.8	2.2
FRVL025-120F	2	7.9	13.0	5.1	7.6	3.8	2.2
FRVL030-120F	2	7.9	13.0	5.1	7.6	3.8	2.2
FRVL040-120F	2	8.2	14.2	5.1	7.6	3.8	2.2
FRVL050-120F	2	9.2	14.9	5.1	7.6	3.8	2.2
FRVL065-120F	2	9.7	14.9	5.1	7.6	3.8	2.2
FRVL070-120F	2	10.6	15.5	5.1	7.6	3.8	2.2
FRVL075-120F	4	10.9	17.0	5.1	7.6	4.1	2.2
FRVL090-120F	2	11.9	15.9	5.1	7.6	3.8	2.2
FRVL100-120F	4	11.5	20.1	5.1	7.6	4.1	2.2
FRVL110-120F	3	13.3	18.3	5.1	7.6	4.1	2.2
FRVL125-120F	4	14.0	21.7	5.1	7.6	4.1	2.2
FRVL130-120F	3	15.5	20.6	5.1	7.6	4.1	2.2
FRVL135-120F	4	16.3	21.7	5.1	7.6	4.1	2.2
FRVL160-120F	3	17.5	22.5	5.1	7.6	4.1	2.2
FRVL185-120F	3	19.9	24.9	5.1	7.6	4.1	2.2
FRVL200-120F	4	23.5	27.9	10.2	7.6	4.1	2.2
FRVL250-120F	3	22.5	27.5	10.2	7.6	4.1	2.2
FRVL300-120F	3	25.5	30.0	10.2	7.6	4.1	2.2
FRVL375-120F	3	29.5	34.0	10.2	7.6	4.1	2.2


NOTE : Specification subject to change without notice.




5. Thermal Derating Curve



6. Typical Time-To-Trip at 23°C



NOTE : Specification subject to change without notice.



7. Material Specification


Lead material : FRVL010-120F~FRVL017-120F Tin plated copper, 24 AWG.
 FRVL020-120F~FRVL090-120F Tin plated copper, 22 AWG.
 FRVL075-120F~FRVL375-120F Tin plated copper, 20 AWG.

Soldering characteristics:MIL-STD-202, Method 208E.

Insulating coating:Flame retardant epoxy, meets UL-94V-0 requirement


8. Part Numbering and Marking System

Part Numbering System



Example

Part Marking System



Warning: -Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.



- PPTC device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
- Avoid contact of PPTC device with chemical solvent. Prolonged contact will damage the device performance.

NOTE : Specification subject to change without notice.